

# LSS



## LED blue light lamp KBL

Device for wall mount or distribution box installation.

### Features:

- no lamp replacement required
- easy installation
- robust sheet steel housing
- no maintenance necessary
- lamp life approximately 10 years
- low power consumption

### Available in two models:

- Version 24N: 24V DC, dimming via pulse width modulation
- Version 230N: 110-250V AC, not dimmable

<b>Illuminants</b>	4x 1100mcd LEDs blue oval / beam pattern ca. 35°x 80°
<b>Protection class</b>	IP 40 SK III
<b>Housing</b>	1,5 mm sheet steel housing / RAL9005 powder coated choosable surface mount or flush mount
<b>Installation</b>	wall mounting on four long holes in rear wall
<b>Power supply</b>	version 24N: 24V DC / 0,02A / 0,48W dimmbare via PWM (pulse width modulation) version 230N: 110-250V AC / 0,02A / 5VA not dimmable cable feeder for both versions via screw connection M16
<b>RoHS-conform</b>	yes
<b>Dimensions</b>	W x D x H 80 x 25 x 80mm (without surface mount housing) W x D x H 80 x 60 x 80mm (with surface mount housing)
<b>Weight</b>	0,17 kg (without leads)
<b>Order numbers</b>	version 24N: L01002 version 230N: L01006 surface mount housing: L01003