



ipMaster

open-source firewall for theater- and studio applications

- Applications:**
- remote management for studio equipment
 - universal firewall for mid-size companies
 - control and monitoring of APC UPS's

- Features:**
- flexible network configuration (red / green / blue / orange)
 - easy administration through web interface, SSL support
 - WAN interface with: DHCP client, PPPoE, PPTP, static IP, and many other interfaces
 - VPN with IPSEC, X.509 certificates (net-to-net or RoadWarrior) with integrated CA
 - Block Out Traffic (filtering of accesses to the outside)

Processor	AMD Geode LX800 with 500 MHz
Compact Flash base	CompactFlash 512MB
Ethernet	2x 10/100 Base-T (IEEE 802.3u, 802.3x) / RJ45 / Auto-Negotiation Auto-MDI/MDIX / front: "green" interface / back: "red" interface
Display	blue text display 20x 4 characters with white LED backlight
Interfaces	front: 1x USB2.0 / COM1 (RS-232) / Ethernet / 2x PS/2 / reset button back: 1x USB2.0 / COM2 (RS-232) / VGA / 24V-I/O / Ethernet
Power supply	100...230V AC single phase / 47...63Hz / power consumption 20W IEC connector (IEC320)
RoHS-conform	yes
Dimensions	W x D x H 448 x 220 x 44mm (19" / 1 U)
Weight	1,9 kg (without leads)
Shipment	ipMaster (19" / 1 U) / Power cord/ Software-CD
Order number	5007