



PowerDim 5K

The *LSS PowerDim 5K* is a thyristor dimmer in a compact shuttle design. Especially in decentralised light system it develops the maximum potential. Full passive cooling on the generously sized ribs and the RDM capabilities make the *PowerDim 5K* to an on-stage dimmer par excellence in the professional theatre and studio operations.

To avoid defects in the *LSS PowerDim 5K* is equipped with safety devices. In addition to permanent overload measurement a constantly running peak test and short-circuit test belongs to it. So damages to the dimmer itself, but also to the lighting system can be avoided.

The *LSS PowerDim 5K* is controlled by DMX512. The control protocol is complemented by the Remote Device Management (RDM) protocol. Thus, configuration and monitoring of the dimmer are available directly at the main console. To increase the reliability, the *PowerDim 5K* features a DMX-hold function. In case of a data loss, the last received data will be held and run.

The *LSS PowerDim 5K* is designed for dimming halogen lamps and all other headlights with incandescent lighting. The *PowerDim 5K* offers 13 dimmer curves and for using halogen lamps it is equipped with a preheat switch is configurable via RDM.

Technical specifications:

Power Supply	230V / AC / 50/60Hz
Nominal current	max. 22A
Minimum load	25W
Hardware connectors and interfaces	Power: CEE Power supply cable (250V/32A) or DBS Deutscher Bühnen Stecker Dimmer output: powerCon black DMX input: 5pin XLR female DMX THRU: 5pin XLR male Other connectors/interfaces on request.
Protocol	DMX512A
Power Output	5 kVA
Internal fuse	25 A circuit breaker type C
Internal monitoring	<ul style="list-style-type: none">- Short circuit monitoring- Temperature monitoring
Temperature warnings/ Over temperature	75°C (167°F)/ 80°C (176°F) (Default settings, manually changeable)
Settings	<ul style="list-style-type: none">- DMX address- 13 dimmer curves- Behaviour in case of data loss- Pre heat
Settings via	2 short stroke buttons, 5 hexadecimal rotary switches, RDM
Rise time	≥ 200µs
Operation temperature	0° to +50°C (32° to 122°F) in vertical position 0° to +40°C (32° to 104°F) in other positions
Weight	5,3 kg
Dimensions (W x L x H)	215 x 350 x 100mm
Order number	L02008