

LSS



LED Duct

The LSS *LED Duct* is a white/blue light lamp in a compact, self-supporting duct construction. The LED duct has a U-profile, which can additionally be used as a cable duct and device carrier for switches and connections. The normal applications are galleries in the backstage, lighting towers, and all other places where energy - efficient and space-saving illumination is desired.

A wide range of accessories is available for the LSS *LED Channel*. This allows to adapt the LED channel to any requirements. For more information, see the product catalogue DUCT Profiles.

The LSS *LED Duct* consists of an extruded aluminium, the surface is powdered matte black (RAL 9005). Other RAL colours are available on request.

Technical specifications:

Luminaires	3W LEDs
Luminous flux	<ul style="list-style-type: none">• Cold-white up to 1800 lumens per LED board• Royal-blue up to 600mW per LED board These values are valid for standard design only. The values may differ for special designs.
Accessories in product catalogue Duct Profiles	<ul style="list-style-type: none">• Covers, duct connections and fittings• Carriers and LEDs• Attachments, glasses and lenses• Power supplies, cable carriers
Protection IP / Appliance class	IP 20 / Class I
Case	Extruded aluminium profile
Colour	RAL 9005 Other colours on request
Power supply	Optionally 230V AC, 24V DC or Power-DMX
RoHS	Conform
Dimensions	W x H in mm 85 x 40
Weight	Body: 1,56kg/m Top Cover: 0,46kg/m
Order number	L04010